

HEATRITE™



Heat-Rite™ Brooders Heat More Efficiently.

Use the Horizon® Whole House Controller™ to easily monitor the temperature of each zone in your house and automatically control the brooders for optimum warming and gas-saving efficiency. In addition to brooders, the Horizon Controller can provide complete computerized management with off-site monitoring for temperature, humidity, ventilation (rates), water, feed, and lighting.



A VAL-CO® Brooder Zone Control Panel uses a single thermostat to regulate all of the brooders in a zone as if they were one. This prevents over or under heating from individual brooders affecting one another. Achieve accuracy and efficiency of temperatures throughout the house using multi-zone control.

The Glow Radiant Brooder from VAL-CO® uses infrared heating technology to quickly and efficiently warm the floor and chicks rather than wasting heat on the air that rises above the brooding area.

Features and Options:

- 34" canopy (86 cm)
- BTU/Hr rating to 40,000 (10,100 k/cal)
- Liquid Propane (LP) or Natural Gas
- Ignition options include the gas-saver horizontal pilot, vertical pilot, and pilot-free direct spark
- Control methods – individual, zone, whole house
- Four individual brooder control options – snap action, modulating, zone, direct spark


Innovative ideas build better brooders:

- Fewer brooders, more efficient heat per brooder – Glow Radiant infrared brooders warm chicks and floor without wasting energy on air.
- Gas efficiency – Pancake brooders with unique horizontal pilot construction stay lit with less gas.
- Safety – patent-pending horizontal pilots with surround-shield protection resist windy situations caused by ventilation fans or minimum vents.
- Easy, trouble-free assembly and cleaning – snap-together pieces. Factory-assembled burners provide quick installation.
- Even heat – unique leveler brackets quickly adjust canopy in two directions – side-to-side and front-to-back.
- Durability – specialized steel components promote heat efficiency and prevent corrosion.






Performance You Can Count On

Heat-Rite Brooder Specifications*

Glow Radiant (Infrared)		
		
CAPACITY:	30,000 BTU/Hr 7,560 k/cal <i>(for altitudes >1000m)</i>	40,000 BTU/Hr 10,080 k/cal
DIMENSIONS:		
WIDTH:	34" - 86 cm	
HEIGHT:	16" - 41 cm	

*Technical specifications may change. Consult your VAL-CO representative for details.

Individual Brooder Control Options

Direct Spark	Robertshaw Zone Control	S.I.T. Snap Action or Modulating Control
		
<p>Use less fuel with no burning pilots. Avoid unnecessary heat when you don't need it. A low voltage electrical source instead of burning pilots reduces maintenance.</p>	<p>Zone controls on individual brooders provide consistent temperatures to be set for a specific area. Brooders can be operated by a brooder zone control panel or a Horizon® Whole House Controller™.</p>	<p>S.I.T. combines a snap-action thermostat with 100% safety cut-off valve. Modulating control provides pre-setting different BTU levels for a more constant level of heat. Brooding temperatures can be set within a range from 70° F to 115° F.</p>

North America:
Phone: 800-99VALCO (800-998-2526)
Fax: (+1) 419-678-2200
E-mail: sales@val-co.com

International:
Phone: (+1) 419-678-8731
Fax: (+1) 419-678-2200
E-mail: intl.sales@val-co.com



Tube Heaters

Efficient Radiant Tube Heaters, with ceiling-mounting, save brooder space and cover long areas.

Space Heaters

Space Heaters warm air for whole house protection and comfort.

