



# Durable and Reliable Feed Delivery.



A double boot, twin transition application for maximum versatility and delivery rate.



The Triple Upper Boot is designed to provide more feed to more flexible auger lines from one source. When used in conjunction with the double lower boot, up to six auger lines can run from a single feed bin!

## Reliable Auger

- With auger manufactured by VAL-CO, in the U.S., the quality control is closely monitored both in-house and at the steel mill.
- High carbon steel is heat treated and tempered to proprietary specifications to ensure long auger life.
- Each batch of auger is microscopically inspected and vigorously tested before it can be approved for shipment.

## Post-forming Proprietary Treatment

- VAL-CO developed an in-line secondary proprietary process to treat the surface of the auger, helping to ensure the auger does not crack.
- This process allows VAL-CO to be confident in standing behind the 10 year warranty (3 years outright, 7 years limited).

## 740 Systems - Extra High Volume

- The 740 System is our largest auger system available today, providing more than double the capacity of our 735 (High Volume) system!



## Feed Delivery Components



Clear, green & semi-translucent boots with double & single transition options.



Poly or steel discharge heads with dependable mechanical or proximity backup sensors.



Volume drops, all-out drops, and more!



Engineered sensors for your application: level & safety switches, tube & hopper mounted.

## Auger Tubing

### Strong Tubes

- Auger tubes are made with a durable material and UV protection on the outside for maximum longevity.
- Die-formed elbows ensure consistent thickness and tight tolerances.



## FLEXIBLE AUGER OPTIONS

**LOW VOLUME** 15 lb (6.8 kg) Per Minute



**PELLET AUGER** 35 lb (15.9 kg) Per Minute



**STANDARD VOLUME** 50 lb (22.7 kg) Per Minute



**HIGH MOISTURE** 50 lb (22.7 kg) Per Minute



**HIGH VOLUME** 100 lb (45 kg) Per Minute



**EXTRA HIGH VOLUME** 220 lb (99.8 kg) Per Minute



Approximate feed delivery rate is based on 40 lbs./cubic foot feed density and 359 rpm drive unit.

Call your local **VAL-CO** representative or distributor for more information on these and our other fine products.

### North America:

Phone: 800-99VALCO (800-998-2526)

Fax: (+1) 419-678-2200

E-mail: sales@val-co.com

### International:

Phone: (+1) 419-678-8731

Fax: (+1) 419-678-2200

E-mail: intl.sales@val-co.com



Performance You Can Count On

www.val-co.com